

ROLL PAPER CUTTER

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention relates to a roll paper cutter for cutting roll paper.

2. Description of the Related Art

10 There is provided a roller cutter type roll paper cutter using a rotary knife for cutting roll paper such as a receipt which has been sent out from a platen.

In the conventional roller cutter type roll paper cutter, a rotary knife is attached to a carriage. A rail along which this carriage is moved also functions
15 as a stationary knife. When the carriage moves on the rail which is fixed, roll paper is cut into sheets by the rotary knife and the rail, that is, roll paper is cut into sheets by the rotary knife and the stationary knife.

Therefore, it is necessary to arrange the
20 components so that the rail, which also functions as a stationary knife, and the rotary knife come into contact with each other at all times. Accordingly, the degree of freedom of arranging the components is limited. As a result, it becomes difficult to replace the roll paper.

25 SUMMARY OF THE INVENTION

It is an object of the present invention to provide a roll paper cutter, the degree of freedom of arranging the components of which is large, so that the replacement of roll paper is not obstructed.

30 The present invention provides a roll paper cutter, for cutting roll paper which is fed out from a roll of paper so that it can be separated from an outer circumference of the roll of paper, comprising: a rail extending, in the longitudinal direction of the rail, perpendicular to the roll paper feeding direction;
35 a stationary knife fixed at, and supported by, a carriage moving along the rail in the longitudinal direction of

the rail; and a rotary knife pivotably supported by the carriage and rotated by coming into contact with the stationary knife when the carriage is moved wherein, when the carriage is moved in the longitudinal direction of the rail, a cutting edge intersection, formed by the rotary knife which is rotated by the movement of the carriage and also formed by the stationary knife, crosses and cuts the roll paper in the width direction.

The present invention may be more fully understood from the description of preferred embodiments of the invention set forth below, together with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view for explaining the first embodiment of the roll paper cutter of the present invention.

Fig. 2 is a cross-sectional view, taken on a cross-section which is perpendicular to the longitudinal axis of the rail, of the roll paper cutter shown in Fig. 1.

Fig. 3 is a view showing a printer into which the roll paper cutter shown in Fig. 1 is incorporated.

Fig. 4 is a view showing a relation between the rotary knife and the stationary knife of the roll paper cutter shown in Fig. 1.

Fig. 5 is a view showing a relation between the rotary knife and the stationary knife of the roll paper cutter of the first variation of the first embodiment of the present invention.

Fig. 6 is a view showing a relation between the rotary knife and the stationary knife of the roll paper cutter of the second variation of the first embodiment of the present invention.

Fig. 7 is a view showing a relation between the rotary knife and the stationary knife of the roll paper cutter of the third variation of the first embodiment of the present invention.

Fig. 8 is a cross-sectional view, taken on a cross-

section which is perpendicular to the longitudinal axis of the rail, of the second embodiment of the roll paper cutter of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

5 Referring to the accompanying drawings, embodiments of the roll paper cutter of the present invention will be explained as follows.

Fig. 1 is a perspective view for explaining a characteristic portion of the roll paper cutter 1 of the first embodiment of the present invention. The roll
10 paper cutter 1 includes a carriage 10 to which the rotary knife 11 and the stationary knife 12 are attached, and this carriage 10 is driven by the screw shaft 30 so that the carriage 10 can be moved along the rail 20 in the
15 direction of an arrow.

The rotary knife 11 is attached to the same shaft as that of the guide roller 13 which travels on the rail 20. Therefore, the rotary knife 11 can be rotated
simultaneously with the guide roller 13. On the other
20 hand, the stationary knife 12 is attached obliquely with respect to the rail 20. The stationary knife 12 has a guide section 12a, which is arranged outside the rail 20 (in an upper portion of the drawing), for guiding the roll paper 5.

25 When the carriage is moved in the left upper direction in the drawing, the cutting edge intersection 14, formed between the rotary knife 11 and the stationary knife 12, is moved from the edge of the roll paper 5 in the width direction in such a manner that the stationary
30 knife 12 crosses the roll paper 5. In this way, the roll paper 5 can be cut off by the cutting edge intersection 14. In this case, a portion of the stationary knife 12 outside the rail 20 (an upper portion of the stationary knife 12 in the drawing) functions as a guide section
35 12a. Therefore, this guide section 12a guides the roll paper 5 into the cutting edge intersection 14 formed between the rotary knife 11 and the stationary knife 12.

0989057-4E404

5
10

15

20

25

30

35

35

of the stationary knife 11 occurs. In order to prevent local abrasion of the stationary knife 11 from occurring, the position of the cutting edge intersection 14 is made to fluctuate by the following variations.

5 In the first variation of the first embodiment shown in Fig. 5, the profile of the rotary knife 11 is a real circle, however, the geometrical center 11c of the rotary knife 11 is offset from the rotary center 13c of the guide roller 13. Due to the above arrangement, the
10 cutting edge intersection 14 is reciprocated between 14A and 14B, that is, the cutting edge intersection 14 is not stopped. Therefore, local abrasion is prevented from occurring.

In the second variation of the first embodiment
15 shown in Fig. 6, the profile of the rotary knife 11 is an ellipse, and the geometrical center 11c of the rotary knife 11 coincides with the rotary center 13c of the guide roller 13. Due to the above arrangement, the cutting edge intersection 14 is reciprocated between 14C
20 and 14D. Therefore, the local abrasion is prevented from proceeding.

In the third variation of the first embodiment shown in Fig. 7, the profile of the rotary knife 11 is a triangle, the corners of which are rounded, and the
25 geometrical center 11c is made to coincide with the rotary center 13c of the guide roller 13. Due to the above arrangement, the cutting edge intersection 14 is reciprocated between 14E and 14F. Therefore, the local abrasion is prevented from proceeding.

30 Fig. 8 is a cross-sectional view showing the second embodiment. When the cross-sectional view showing the second embodiment is compared with the cross-sectional view of Fig. 2 showing the first embodiment, the carriage 10 is attached upside down. Therefore, the rotary knife
35 11 and the stationary knife 12 are arranged closer to the platen 50 than the rail 20. Due to the above arrangement, even if the roll paper 5 is strongly curled,

the cutting edge intersection 14 is capable of positively catching an end portion of the roll paper 5 in the width direction.

5 According to the structure of the present invention, it is unnecessary for the rail to function as a stationary knife. Therefore, a large degree of freedom can be provided for designing the arrangement.

0909057-116101